

Chela Ltd

78 Bilton Way • Enfield • Middlesex EN3 7LW • UK
Tel +44 (0)20 8805 2150 • Fax +44 (0)20 8443 1868
E-mail mail@chela.co.uk • Website www.chela.co.uk

Packing and Shipping Information

It is available in the following container sizes:

4x5 Litre 25 Litre 200 Litre

Type of container	Net weight (kg)	Gross weight (kg)	Size (mm) (hx d) or (hx wxd)
5 l plastic	5.35	5.60	255 x 190 x 140
25 l plastic	26.75	27.85	420 x 290 x 260
200 l plastic	214	222	920 x 590

Specification

Appearance:	clear thin liquid
Colour:	Pale straw
Odour:	Eucalyptus
S.G.:	1.07
pH:	12.5-13.3

Hazard Identification

Risk & Safety:	Irritant
Hazard Symbols:	Xi

First-aid Measures

Inhalation:	Not applicable
Eyes:	Rinse immediately with plenty of water.
Skin:	Wash skin thoroughly with plenty of water.
Ingestion:	Do not induce vomiting. Drink plenty of water. Get medical attention if any discomfort continues.

Consult the Safety Data Sheet for full Health and Safety information.

Di-Aqua®**Aqueous System for the Removal of Silicone Residues and other difficult contaminants**

Di-Aqua® will effectively emulsify silicone oils, greases and uncured elastomers as well as adhesive tape residues. Its specialist cleaning action will also quickly and efficiently remove ordinary oils, greases, rubber residues and soils. Di-Aqua® has been formulated with the environment in mind and does not contain chlorinated, fluorinated, aromatic or hydrocarbon solvent. The detergents used are biodegradable and no phosphates are present. It is economical in use as well as being efficient and can be diluted with up to 9 parts water.

Benefits of Di-Aqua®

- Effectively emulsifies silicone oils, greases and uncured elastomer
- Environmentally considerate
- Water based
- Non-flammable
- Wide range of applications
- Leaves silicone-free surface
- Removes Rubber residues from concrete
- Excellent cleaner for normal soils

Application

Di-Aqua® can be used to remove silicone oils, greases, prepolymer, uncured elastomer as well as adhesive tape residues from all manner of surfaces including floors, equipment and printed circuit boards. As well as being a specialist cleaner for silicone oils, Di-Aqua® is an excellent general purpose cleaner for surfaces that are not damaged by water.

Di-Aqua® can be used in any area where silicone oils need to be removed including silicones that are used in the personal care products.

**This is just one product
from the Digesil® range**

Methods of use

Silicone and difficult contaminants

Floors and Equipment

Dilute 1 part Di-Aqua® to 9 parts water. Apply the diluted Di-Aqua® and scrub or mop as convenient. Use a scrubbing machine for large areas.

Process vessels

Dilute 1 part Di-Aqua® to 9 parts of water. Then either fill process vessel and clean using cleaning in place system or spray onto surface and rinse off.

Contaminated Parts

Dilute 1 part Di-Aqua® to 9 parts of water. Either immerse contaminated part in Di-Aqua®, soak for few minutes and rinse off or spray and leave for a few minutes and rinse off.

General Cleaning

Depending on the level of soiling, Di-Aqua, can be diluted with up to 80 parts of water.