

Chela Ltd

78 Bilton Way • Enfield • Middlesex EN3 7LW • UK
Tel +44 (0)20 8805 2150 • Fax +44 (0)20 8443 1868
E-mail mail@chela.co.uk • Website www.chela.co.uk

Packing and Shipping Information

It is available in the following container sizes:

5 Litre 25 Litre

Type of container	Net weight (kg)	Gross weight (kg)	Size (mm) (h x w x d)
5 l plastic	5.05	5.3	255 x 190 x 140
25 l plastic	25.25	26.35	420 x 290 x 260

Specification

Appearance:	Liquid
Colour:	Straw
Odour:	Lemon
S.G.:	1.01

Hazard Identification

Risk & Safety:	Not classified as hazardous under current legislation
Hazard Symbols:	Not applicable

First-aid Measures

Inhalation:	Not applicable
Eyes:	Promptly wash eyes with plenty of water. Rinse for at least 15 minutes. Get medical attention if any discomfort continues.
Skin:	Not applicable
Ingestion:	Do not induce vomiting. Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort continues.

Consult the Safety Data Sheet for full Health and Safety information.



CERT NO FS60515

Chela Ltd is a
BS EN ISO9002:1994
registered organisation

Dicone Aqua

Dicone Aqua is a powerful water based cleaner for the removal of surface contaminants such as oil, grease and general dirt from metals, plastics and glass. Dicone Aqua leaves the surface clean and residue free ready for finishing or bonding. Suitable replacement for Isopropyl alcohol.

Also available as impregnated wipe

Benefits of Dicone Aqua

- Non-hazardous
- Water based
- Low VOC
- Highly efficient
- Leaves no residues
- Zero solids
- Removes oils, greases, dirt and adhesive residues
- Non flammable

Applications

Dicone Aqua can be used for:

- panel cleaning,
- preparation of joints before sealing or bonding,
- metal, plastic and glass cleaning and degreasing .

Chela: Innovative Cleaning Solutions and Technical Care

Chela Product Code: 602

Method of use

1. Wet clean cloth with Dicone Aqua
2. Wipe over area to be cleaned folding cloth to present clean cloth when necessary.

**This is just one product
from the Digesil® range**