

Chela Ltd.

78 Bilton Way • Enfield • Middlesex EN3 7LW • UK
 Tel +44 (0)20 8805 2150 • Fax +44 (0)20 8443 1868
 E-mail mail@chela.co.uk • Website www.chela.co.uk

Packing and Shipping Information

Eurowash® ISR Foam is classed as non-hazardous for shipment by air, sea, rail and road.

It is available in the following container sizes.

25 litre	200 litre	1000 litre	
Type of container	Net weight (kg)	Gross weight (kg)	Size (mm) (h x d) or (h x w x d)
25 l plastic	25.87	26.97	420 x 290 x 260
200 l plastic	207	215	920 x 590
1000 l plastic	1035	1110	1140 x 1206 x 1000

Specification

Appearance:	Viscous Liquid
Colour:	Opaque slightly yellow
S.G.:	1.035
pH :	2
Foam:	Medium
Surfactants	Non-ionic
Antistatic, glossing aid	Cationic

Hazard Identification

Risk & Safety:	Irritant
Hazard Symbols:	Xi

First-aid Measures

Inhalation:	Not applicable
Eyes:	Irrigate with water for at least 15 minutes.
Skin:	Wash contaminated area thoroughly with mild soap.
Ingestion:	Rinse mouth with water.

Consult the Safety Data Sheet for full Health and Safety information.

Chela Ltd is a
 BS EN ISO9002:1994
 registered organisation

Chela Product Code:**Eurowash® ISR Foam**

Eurowash® ISR Foam is a high performance concentrated train cleaner designed specifically for use through foam arch equipment. Eurowash® ISR Foam utilises a synergistic blend of surfactants and acids to give a high quality foam that clings to the train surface giving extended dwell time.

A unique blend of acids specifically formulated for the fast and effective removal of iron stains from rolling stock. Eurowash® ISR Foam will leave surfaces clean and streak free.

Eurowash® ISR Foam will remove iron brake dust, general grime, tunnel dirt, oil, scale and metallic pollution without damaging the paintwork. It uses an antistatic agent which leaves the vehicle with a bright sheen which resists soiling and makes subsequent cleaning easier.

Eurowash® ISR Foam has been independently assessed by Scientifics as fit for purpose. Benefits of using Eurowash® ISR Foam

- High quality cleaning foam
- Concentrated - high performance at high dilution
- Free rinsing - no unsightly hard water stains
- Foam minimises use of chemical
- Removes iron brake dust
- Contains antistatic gloss shine that makes subsequent cleaning easier
- Very quick and effective
- Improved rinsing and sheeting on glass
- Leaves surfaces clean, streak-free and shiny
- Effective at low temperatures
- Effective in hard or soft water
- Removes old thick build up of iron dust
- Removes oil and grease
- Lifts off ordinary soil and grime
- Environmentally considerate

Safety & Environment

Eurowash® ISR Foam has been developed with the environment in mind.

- Irritant under EU legislation
- Uses biodegradable surfactants
- Does not contain, NTA, EDTA or HEDTA
- Does not use alkyl phenol ethoxylates

Dilutions

May be diluted with as much as 40 volumes (2.5% v/v) of water depending on degree of soiling.

Method of use

Automatic Brush Wash

Ensure that the dosing pump has been calibrated for dilution at the appropriate rate. Carry out cleaning as specified by the brush wash manufacturer.

Foam Arch

Dilution will be set up for each individual customer.

Product Endorsements

Eurowash® ISR Foam has been tested to their material compatibility protocol by Scientifics Ltd and been shown to be suitable for use in the rail industry.

A copy of the full report is available on request.