

Chela Ltd.

78 Bilton Way • Enfield • Middlesex EN3 7LW • UK
 Tel +44 (0)20 8805 2150 • Fax +44 (0)20 8443 1868
 E-mail mail@chela.co.uk • Website www.chela.co.uk

Packing and Shipping Information

Eurowash® ISR Thick is non-hazardous for shipment by air, sea, rail and road. It is available in the following container sizes.

25 litre	200 litre	1000 litre	
Type of container	Net weight (kg)	Gross weight (kg)	Size (mm) (h x d) or (h x w x d)
25 l plastic	25.87	26.97	420 x 290 x 260
200 l plastic	207	215	920 x 590
1000 l plastic	1035	1110	1140 x 1206 x 1000

Specification

Appearance:	Viscous Liquid
Colour:	Opaque slightly yellow
S.G.:	1.035
pH :	2
Foam:	Medium
Surfactants	Non-ionic
Antistatic, glossing aid	Cationic

Hazard Identification

Risk & Safety:	Not classified as hazardous under current legislation
Hazard Symbols:	Not applicable

First-aid Measures

Inhalation:	Not applicable
Eyes:	Irrigate with water for at least 15 minutes.
Skin:	Wash contaminated area thoroughly with mild soap.
Ingestion:	Rinse mouth with water.

Consult the Safety Data Sheet for full Health and Safety information.



Chela Ltd is a
 BS EN ISO9002:1994
 registered organisation

CERT NO. FS60515

Eurowash® ISR Thick

A unique blend of acids specifically formulated for the fast and effective removal by manual cleaning of iron stains from rolling stock. Eurowash® ISR Thick will leave surfaces clean and streak free. Eurowash® ISR Thick has been assessed by Scientifics as fit for purpose.

Benefits of using Eurowash® ISR Thick

- Very quick and effective
- Thick so it clings - easy to use.
- Improved rinsing and sheeting on glass
- Leaves surfaces clean, streak-free and shiny
- Effective on low temperatures
- Effective in hard or soft water
- Easily applied by brush
- Removes old thick build up of iron dust
- Removes oil and grease, ordinary soil and grime

**Before****After**

Chela: Innovative Cleaning Solutions and Technical Care

Chela Product Code: 226

Safety & Environment

Eurowash® ISR Thick has been developed with the environment in mind.

- Not classified as hazardous under current legislation
- Uses biodegradable surfactants
- Does not contain, NTA, EDTA or HEDTA
- Does not use alkyl phenol ethoxylates

Dilutions

For heavy soil use neat as supplied.

May be diluted with as much as 9 volumes (10% v/v) of water depending on degree of soiling.

Method of use

Hand

Apply neat or diluted product with a brush. Agitate and allow to dwell for up to 15 minutes dependant upon soiling. Usually a few minutes is enough. Agitate again and brush rinse with low pressure water. Always use clean equipment.

Product Endorsements

Eurowash® ISR Thick has been tested to their material compatibility protocol by Scientifics Ltd and been shown to be suitable for use in the rail industry.

A copy of the full report is available on request.