

## Chela Ltd

78 Bilton Way • Enfield • Middlesex EN3 7LW • UK  
Tel +44 (0)20 8805 2150 • Fax +44 (0)20 8443 1868  
E-mail mail@chela.co.uk • Website www.chela.co.uk

## Packing and Shipping Information

Eurowash® 1000 is non-hazardous for shipment by air, sea or road. It is available in the following container sizes:

25 litre                      200 litre                      1000 litre

Type of container	Net weight (kg)	Gross weight (kg)	Size (mm) (h x w x d)
25 l plastic	25.75	26.85	420 x 290 x 260
200 l plastic	206	214	920 x 590 (h x d)
1000 l plastic	1030	1105	1140 x 1206 x 1000

## Specification

Appearance:	Liquid
Colour:	Straw
Odour:	Eucalyptus
S.G.:	1.03
pH:	9.7 (1% dilution)
Foam Height:	10 ml (1% dilution)
Surfactant Type:	Nonionic, amphoteric
Builders:	Organic complexing agents

## Hazard Identification

Risk & Safety:	Not classified as hazardous under current legislation
Hazard Symbols:	Not Applicable

## First-aid Measures

Inhalation:	Not applicable
Eyes:	Irrigate with water for at least 15 minutes
Skin:	Rinse contaminated area with plenty of water
Ingestion:	Give plenty of water to drink

Consult the Safety Data Sheet for full Health and Safety information.

Chela Ltd is a  
BS EN ISO9002:1994  
registered organisation

## Eurowash® Super Sheen

**New technology has been used to create a high performance, mildly alkaline cleaner that imparts a sheen to paint and glass that both reduces spotting and helps to prevent resoiling.**

**It can be used in automatic brush washes and manually. Removes traffic film, brake dust, dirt, grease and other similar soil from the body work of rail carriages.**

## Benefits of using Eurowash® Super Sheen

- Paint and glass gleam
- Reduces spotting
- Trains stay clean longer
- Helps prevent resoiling
- No cationic surfactant
- Economic in use
- Works in hard or soft water
- High dilution

Chela: Innovative Cleaning Solutions and Technical Care

**Chela Product Code: 1122**

## **Application of Eurowash® Super Sheen**

For light soiling, dilute Eurowash® Super Sheen to 0.5% (1:200).

For normal soiling, dilute Eurowash® Super Sheen to 1% (1:100).

For heavy soiling, dilute Eurowash® Super Sheen to 2% (1:50).

## **Automatic Brush Wash**

Ensure that the dosing pump has been calibrated for dilution at the appropriate rate. Carry out cleaning as specified by the brush wash manufacturer.

## **Pressure Washer**

Using a low pressure, apply Eurowash® Super Sheen at the appropriate dilution. Start from the lower sections of the carriage and work up towards the roof. If necessary, agitate the surface with a soft brush to loosen tenacious soiling matter. Rinse off using a high pressure working down from the roof.

## **By Hand**

Dilute Eurowash® Super Sheen to the appropriate level. Apply the diluted product with a soft brush, start from the lower sections of the carriage and work up towards the roof. Let the solution dwell for a few minutes then agitate the surface, work systematically from the lower sections up towards the roof. Rinse off with clean water, working from the roof down towards the lower sections.