

Chela ltd
78 Bilton Way Enfield Middlesex EN3 7LW UK
Tel +44 (0) 20 8805 2150 Fax +44 (0) 20 8443 1868
E-mail mail@chela.co.uk Website www.chela.co.uk

Packing and Shipping Information

Marathon Acrylic Floor Seal is non hazardous for shipment by air, sea, road and rail. It is available in the following container sizes:

5 litre
25 litre
200 litres

Specification

Appearance: Thin, mobile, opaque liquid
Colour: White
Odour: Mild
S.G: 1.030
pH: 9.0

Hazard Identification

Risk & Safety: Not classified as hazardous under EU legislation
Hazard Symbols: Not applicable

First-aid Measures

Inhalation: Not applicable
Eyes: Irrigate with water for at least 15 minutes. Seek medical attention
Skin: Rinse contaminated area with plenty of water
Ingestion: Give plenty of water to drink

Consult the Safety Data Sheet for full Health and Safety information.

Marathon Acrylic Floor Seal

A permanent acrylic emulsion seal for use on hard and soft floors including: marble, terrazzo, limestone, concrete, pavers, sheet PVC, PVC tiles, asphalt and linoleum.

Marathon Acrylic seal gives a tough easy-to-clean surface that is non-yellowing. It may be used for exterior as well as interior use. A good base for Marathon and other emulsion polishes. It is not removed by normal emulsion polish strippers.

Benefits of using Marathon Acrylic Seal

Emulsion system low VOC
Water based low odour for operator and customer comfort
Low odour does not taint
Quick drying can be walked on in as little as one hour
Solvent free no flash point, safer to use
Solvent free equipment cleaned with water
Masonry floors made easy to clean
Resists polish strippers and is a good economical base for emulsion polish
Non-yellowing original colour of floor maintained
Seals porous floors and saves unnecessary coats of emulsion polish

Safety & Environment

Non hazardous for us under EU legislation.
Aqueous system means low VOC
Free from aromatic, aliphatic and ketonic solvents

Application of Marathon Acrylic Seal

Use clean equipment and apply to a clean floor. Once applied Marathon Acrylic Seal cannot be removed. Use neat, do not dilute.

Coverage: Concrete and porous floors 5 sq meters
 per litre.
 Low porosity floors 20 sq meters per litre

The floor to be sealed must be free of debris, clean and dry. Sweep or vacuum to remove loose soil. Clean thoroughly with Guardisan Deep Fresh rinsing well with clean water. Use a wet pick-up-vac for best results. Imbedded oil and grime can be removed from concrete floors using an acidic cleaner.

Pour Marathon Acrylic Seal on to the floor and spread with a brush, mop or polish applicator. Do not generate foam and do not allow to puddle. When dry apply another coat if required.

Dampen mops or polish applicator before use. Do not use cheap mops containing cotton seeds. When using on soft floors such as PVC use Marathon Emulsion polish as part of the maintenance programme. This will help prevent localised wear of the Acrylic Seal.

Product Endorsements

Marathon Acrylic seal has been tested by the Fisher Research laboratory and found to be an excellent seal for the applications mentioned above. In addition Marathon Acrylic Seal has been sold by Fisher Research Limited for over ten years and it has given excellent and reliable results