

Chela Ltd

78 Bilton Way • Enfield • Middlesex EN3 7LW • UK
Tel +44 (0)20 8805 2150 • Fax +44 (0)20 8443 1868
E-mail mail@chela.co.uk • Website www.chela.co.uk

Packing and Shipping Information

It is available in the following container sizes: 5 litre

Type of container	Net weight (kg)	Gross weight (kg)	Size (mm) (h x w x d)
5 l plastic	6	6.25	255 x 190 x140

Specification

Appearance:	Paste
Colour:	Terracotta
Odour:	Odourless
S.G:	1.2

Hazard Identification

Risk & Safety:	Irritating to eyes
Hazard Symbols:	Xi

First-aid Measures

Inhalation:	Move the exposed person to fresh air. Rinse nose and mouth with water. Get medical attention if irritation persists.
Eyes:	Promptly wash eyes with plenty of water. Get medical attention if irritation persists.
Skin:	Wash the skin with soap and water. Seek medical attention if irritation persists.
Ingestion:	Rinse mouth thoroughly. Drink plenty of water. Get medical attention.

Consult the Safety Data Sheet for full Health and Safety information.

Chela Ltd is a
BS EN ISO9002:1994
registered organisation

Chela Product Code: 455

**Renew + 1
Interior and Exterior Panel Renovator**

Renew + 1 quickly and safely removes ingrained dirt, stains, graffiti shadow and graffiti including leather dye. It is suitable for use on painted and metal surfaces and its unique action removes even the most stubborn ingrained dirt and graffiti.

The product is a paste slightly perfumed suitable to cling onto vertical surfaces. It has a low hazard classification which make it easy to handle. Its viscosity allows to treat area with relatively small quantities of product.

Areas of application include train and bus interiors and exteriors, road signs and any painted or metal surface.

Benefits of using Renew + 1

- Quick acting and effective
- Removes dirt, graffiti and shadow including leather dye
- Economical in use
- Easy to use paste consistency
- Refreshes and revives surface
- Environmentally responsible

Chela: Innovative Cleaning Solutions and Technical Care

Application of Renew +1

All Surfaces

Shake the bottle.

Paint onto surface with soft bristle brush.

Allow contact time of between 1-5 mins.

Do not allow the surface to dry.

Wipe off residue with a cloth.

Rinse off with clean water or 1% Guardisan Fresh.